



BGAN terminals

A quick reference guide



Inmarsat's Broadband Global Area Network service – BGAN – is accessible via a small, lightweight, satellite terminal, which is quick to set up and easy to use. And you can use the same device worldwide.

A range of terminals is available, including vehicular systems, providing performance options to suit different operational needs. The service is accessed via BGAN LaunchPad, a software interface, which is standard across all terminals.

					
Wideye™ Sabre™ I Voice and data, single-user device	EXPLORER® 110 Smallest, lightest device in the range	EXPLORER® 300 Highly compact, robust device	EXPLORER® 500 High bandwidth, highly portable device	HUGHES 9201 High performance, multi-user device	EXPLORER® 700 Multi-user device with extensive functionality

Terminals	Manufacturer:	Addvalue Communications www.wideye.com.sg	Thrane & Thrane www.thrane.com	Thrane & Thrane www.thrane.com	Thrane & Thrane www.thrane.com	Hughes Network Systems www.hughes.com	Thrane & Thrane www.thrane.com
	Size:	259 x 195mm (1.6kgs)	200 x 150mm (1kg)	217 x 168mm (1.4kgs)	218 x 217mm (1.4kgs)	345 x 275mm (2.8kgs)	297 x 399mm (3.2kgs)
	Standard IP:	Up to 240/384kbps (send/receive)	Up to 240/384kbps (send/receive)	Up to 240/384kbps (send/receive)	Up to 448/464kbps (send/receive)	Up to 492kbps (send & receive)	Up to 492kbps (send & receive)
	Streaming IP: (send & receive)	32, 64kbps	32, 64kbps	32, 64kbps	32, 64, 128kbps	32, 64, 128, 256kbps, BGAN X-Stream™	32, 64, 128, 256kbps, BGAN X-Stream™
	Voice:	Via RJ-11 or Bluetooth handset/headset	Via RJ-45 or Bluetooth handset	Via RJ-11 or Bluetooth handset/headset	Via RJ-11 or Bluetooth handset or 3.1kHz audio	Via RJ-45 ISDN handset, ISDN TA with two RJ-11 ports for voice or 3.1kHz for audio / fax	Via two RJ-11 ports for voice or 3.1kHz audio / fax, Bluetooth
	ISDN:	N/A	N/A	N/A	64kbps via USB	64kbps via RJ-45	64kbps via RJ-45
	Other data interfaces:	Ethernet, Bluetooth	Ethernet (with adapter), USB, Bluetooth	Ethernet, Bluetooth	Ethernet, USB, Bluetooth	Ethernet, USB, WLAN 802.11b	2 x Ethernet, USB, Bluetooth, WLAN 802.11 a/b/g, Digital I/O
	Ingress protection:	IP 54	IP 44	IP 54	IP 54	IP 55	IP 52 (terminal), IP 66 (antenna)



VRT-100

Rugged, multi-user device for government users



RF-7800B-DU024

Rugged, integrated, high performance system

Customised terminals

Manufacturer:	ViaSat Inc. www.viasat.com	Harris Corporation www.harris.com
Size:	Terminal 287 x 420mm (6.9kgs) Antenna 430 x 275 (2.6kgs)	240 x 240mm (2.8kgs)
Standard IP:	Up to 240 / 384kbps (send / receive)	Up to 448 / 464kbps (send / receive)
Streaming IP: (send & receive)	32, 64kbps	32, 64 & 128kbps
Voice:	Via 5/6 pin audio, RJ-11, ISDN handset	Via military standard connector for normal voice, ISDN standard voice and 3.1kHz for audio / fax
ISDN:	N/A	64kbps via RJ-45
Other data interfaces:	Ethernet, USB	Ethernet, USB via military standard connector
Ingress protection:	IP 67	MIL-STD-810F, IP67



EXPLORER® 727

Multi-user device with extensive functionality



HUGHES 9250

Multi-user device with wireless capability



RF-7800B-VU104

Rugged, integrated, high performance system

Vehicular terminals

Manufacturer:	Thrane & Thrane www.thrane.com	Hughes Network Systems www.hughes.com	Harris Corporation www.harris.com
Size:	Terminal 247 x 270mm (2.5kgs) Antenna 477 x 160mm (6kgs)	Terminal 275 x 345mm (2.8kgs) Antenna 477 x 153mm (5kgs)	Integrated antenna and terminal: 510 x 200mm (12.6kgs)
Standard IP:	Up to 492kbps (send & receive)	Up to 492kbps (send & receive)	Up to 492kbps (send & receive)
Streaming IP: (send & receive)	32, 64, 128 & 256kbps*	32, 64, 128 & 256kbps*	32, 64, 128, 256kbps*
Voice:	Via two RJ-11 ports for voice or 3.1kHz for audio / fax	Via RJ-45 ISDN handset, ISDN TA with two RJ-11 ports for voice or 3.1kHz for audio / fax	Via military standard connector for normal voice, ISDN standard voice and 3.1kHz for audio / fax
ISDN:	64kbps via RJ-45**	64kbps via RJ-45**	64kbps via RJ-45**
Other data interfaces:	4 x Ethernet	Ethernet, WLAN 802.11b	Ethernet, USB via military standard connector
Ingress protection:	IP 31 (terminal), IP 56 (antenna)	IP 55 (terminal), IP 56 (antenna)	MIL-STD-810F, IP67

* Inmarsat supports 256kbps streaming at elevations above 45 degrees. Below this elevation, only the 128kbps streaming connection is available.

** Depending on location. Inmarsat supports ISDN at elevations above 20 degrees.

Whilst the above information has been prepared by Inmarsat in good faith, and all reasonable efforts have been made to ensure its accuracy, Inmarsat makes no warranty or representation as to the accuracy, completeness or fitness for purpose or use of the information. Inmarsat shall not be liable for any loss or damage of any kind, including indirect or consequential loss, arising from use of the information and all warranties and conditions, whether express or implied by statute, common law or otherwise, are hereby excluded to the extent permitted by English law. INMARSAT is a trademark of the International Mobile Satellite Organisation, Inmarsat LOGO is a trademark of Inmarsat (IP) Company Limited. Both trademarks are licensed to Inmarsat Global Limited. © Inmarsat Global Limited 2009. All rights reserved. BGAN terminals October 2009.