

C/Ku Band, 4 Port Feeds



FEED-4CKU
FEED-4CKU-EXT
FEED-4CKU-WB
FEED-4CCKU

- Receive Only 4 Port C/Ku band Prime Focus Feed
- Simultaneous Reception of Dual C & Dual Ku-Band Polarities
- New Extended C/Ku Band Model (FEED-4CKU-EXT)

SPECIFICATIONS	C Band	Ku Band
Frequency:		
FEED-4CKU	3.7 – 4.2GHz	11.70 - 12.75GHz
FEED-4CKU--WB & FEED-4CCKU	3.7 – 4.2GHz	10.95 – 12.75GHz
FEED-4CKU-EXT	3.4 - 4.2 GHz	10.70 – 12.75GHz
VSWR (Typical)		
FEED-4CKU, FEED-4CKU-WB & FEED-4CCKU	1.6:1	1.4:1
FEED-4CKU-EXT	1.7:1	1.6:1
Isolation (Linear)	18 dB	25 dB
Number of Ports	2	2
Type of Ports	WR229	WR75
Polarization:		
FEED-4CKU, FEED-4CKU-EXT, FEED-4CKU-WB	Linear	Linear
FEED-4CCKU	Linear	Circular
Weight	3.0 Lbs approx	

FEATURES:



FEED-4CKU-EXT

- Simultaneous Reception of Dual C & Dual Ku-Band Polarities
- Universal Mounting - Mounts to single pole, tripod and quadpod feed supports
- For use with new antennas or upgrading existing antennas in the field
- Precision cast aluminum construction
- All Components Weather Resistant
- Stainless Steel Hardware
- Microwave transparent throat cover
- Durable flake resistant coating
- Made in the USA

FEED-4CKU_REV005

Specifications are subject to change without notice