

## 9900 Series Frequency Converters



The MITEQ frequency converters are designed for advanced satellite communication systems and are available for a wide variety of frequency plans. Phase noise, amplitude flatness and spurious outputs have been optimized to provide the user with a transparent frequency conversion for all video and data applications.

A strong feature set of monitor and control functions supports powerful local and remote control. Among the features are control of frequency, attenuation and 64 memory locations for each converter where various setups can be stored and recalled.

A continuously updated log of time-stamped records of activity is also provided.

### Features

- Supports expandable NSU 1:N Switchover Series (D-323)
- Amplitude slope adjust
- Three monitor and control ports:
  1. RS485/RS422 remote interface (J6A) changes to RS232 with Option 17C
  2. RS485/RS422 control interface (J7) is provided for use with NSU redundancy system (D-323) or as an alternative interface
  3. 10/100Base-T Ethernet interface (J6B)
- RF, IF and LO monitor ports
- Automatic switching to external 5/10 MHz reference and electronic adjust of internal reference frequency
- Low intermodulation distortion
- Better than IESS-308/309 compliant phase noise
- 64 programmable memory locations
- 30 dB level control
- External alarm input via contact closure
- Time and date stamped event log
- CE Mark

RF Frequency (GHz)	Model Numbers
<b>Upconverters</b>	
5.725 - 6.725	U-9953-6-1K
13.75 - 14.8	U-9956-6-1K
<b>Downconverters</b>	
3.4 - 4.2	D-9901-1-1K
10.7 - 12.75	D-9908-6-1K


### Options

- Higher stability reference
- Remote RS232
- 140 MHz IF frequency
- 50 ohm IF impedance
- Type "N" RF connector (C-Band converters only)


Specifications	Upconverter	Downconverter
Type	Dual conversion	
Frequency step size	1 kHz	
Frequency sense	No inversion	
Input characteristics		
Frequency	70 ±20 MHz (140 ±40 MHz Option 4)	Refer to model number table
Impedance	75 ohms (50 ohms Option 15)	50 ohms
Return loss	26 dB minimum (70 ±20 MHz), 20 dB minimum (140 ±40 MHz)	21 dB minimum
Signal monitor	-20 dBc nominal	
Input level (non-damage)	+15 dBm maximum	
Output characteristics		
Frequency	Refer to model number table	70 ±20 MHz (140 ±40 MHz Option 4)
Impedance	50 ohms	75 ohms (50 ohms Option 15)
Return loss	21 dB minimum	26 dB minimum (70 ±20 MHz), 20 dB minimum (140 ±40 MHz)
Signal monitor	-20 dBc nominal	
Power output (P1 dB)		
C-band	+16 dBm minimum/17 dBm typical	
Ku-band	+10 dBm minimum/12 dBm typical	+16 dBm minimum/17 dBm typical
Transfer characteristics		
Gain	+31–34 dB at 23°C	+44-48 dB at 23°C
Noise figure at min. atten.	14 dB maximum	11 dB maximum
Noise power density	-125 dBm/Hz maximum	N/A
Image rejection	N/A	80 dB minimum
Level stability	±0.25 dB/day maximum at constant temperature ±0.5 dB typical from 0 to 50°C	
Amplitude response	±0.3 dB maximum/40 MHz, ±0.45 dB maximum/80 MHz (140 ±40 MHz Option 4)	
Slope adjust	±1 dB typical in 0.2 dB steps	
Group delay (70 ±18 MHz)		
Linear	0.03 ns/MHz maximum (15 to 50°C)	
Parabolic	0.01 ns/MHz <sup>2</sup> maximum (15 to 50°C)	
Ripple	1 ns peak-to-peak maximum	
Group delay (140 ±36 MHz)		
Linear	0.025 ns/MHz maximum (15 to 50°C)	
Parabolic	0.0035 ns/MHz <sup>2</sup> maximum (15 to 50°C)	
Ripple	1 ns peak-to-peak maximum	
Intermodulation distortion (third order)		
C-band	Two signals each at 0 dBm output 55 dBc minimum (+27.5 dBm IP3 pt.)	Two signals each at 0 dBm output 60 dBc minimum (+30 dBm IP3 pt.)
Ku-band	45 dBc minimum (+22.5 dBm IP3 pt.)	60 dBc minimum (+30 dBm IP3 pt.)
AM/PM conversion	0.1°/dB maximum to 0 dBm output	
Gain slope	0.03 dB/MHz typical, 0.05 dB/MHz maximum (10 MHz minimum)	
Frequency stability	±2 x 10 <sup>-8</sup> , 0 to 50°C (higher stability options available) ±5 x 10 <sup>-9</sup> /day typical (fixed temperature after 24 hour on time)	
Frequency accuracy	C-band: ±10 Hz, Ku-band: ±22 Hz, maximum using external reference	
Spurious outputs		
Signal related	65 dBc up to 0 dBm output	
Signal independent	-80 dBm maximum	
LO leakage at RF port	-75 dBm maximum	-80 dBm maximum
Gain adjustment	30 dB in 0.2 dB steps	
Upconverter mute	80 dB minimum	N/A
External reference	5 or 10 MHz, +4 ±3 dBm Unit will automatically switch to internal reference if external reference level falls below +1 dBm nominal	
Phase noise	See graph	
Remote interface	RS485/RS422: 2 ports user selectable each port (1 port with Option 17C) Ethernet interface: HTTP based web server, SNMP 1.0 configuration, Alarm reporting via SNMP trap, Telnet access, Password protection	

Note: All specifications guaranteed at maximum gain unless otherwise noted.

Representative Block Diagrams



Upconverter




Downconverter

Phase Noise Specifications

Maximum External Reference To Achieve Above Phase Noise

Model	10	100	1K	10K	100K
All Systems	-120	-150	-160	-160	-160

MAXIMUM PHASE NOISE CHARACTERISTICS (1.0 Hz BANDWIDTH)



Options

- 4. 140 MHz IF frequency.
- 10. Higher frequency stability reference.
  - B.  $\pm 5 \times 10^{-9}$ , 0 to 50°C,  $1 \times 10^{-9}$ /day typical (fixed temperature after 24 hour on time).
  - C.  $\pm 2 \times 10^{-9}$ , 0 to 50°C,  $1 \times 10^{-9}$ /day typical (fixed temperature after 24 hour on time).
- 15. 50 ohm IF impedance.
- 17. Remote control.
  - C. RS232 remote interface.
- NRF. Type N-female RF connector (Note: Monitor remains SMA female).

Notes: Missing option numbers are not applicable for this product. For literature describing Local control (front panel) and remote control (bus protocols), refer to MITEQ's Technical Note 25T063.

Protocols are backwards compatible with Technical Notes 25T010 and 25T009.

# 9900 Series Frequency Converters

## General Specifications

### Primary Power Requirements

Voltage .....	90-250 VAC
Frequency .....	47-63 Hz
Consumption .....	25 W typical

### Physical

Weight .....	12 pounds nominal
Chassis dimensions .....	19" x 1.75" panel height x 20" maximum
Connectors	
RF .....	SMA female (N female, Option NRF)
RF monitor .....	SMA female
IF .....	BNC female
IF monitor .....	BNC female
LO monitors .....	SMA female
Alarm .....	DE-9P
External reference .....	BNC female
Remote interface .....	DE-9S for RS485, RS422 and RS232, RJ-45 female for Ethernet
Primary power input .....	IEC-320
Auxiliary control interface .....	DE-9S

### Environmental

Operating	
Ambient temperature .....	0 to 50°C
Relative humidity .....	Up to 95% at 30°C
Atmospheric pressure .....	Up to 10,000 feet
Nonoperating	
Ambient temperature .....	-50 to +70°C
Relative humidity .....	Up to 95% at 40°C
Atmospheric pressure .....	Up to 40,000 feet
Shock and vibration .....	Normal handling by commercial carriers

## Typical Rear Panel View



RSM Switch Module Location  
(see D-233 for more information)