

# 1200

# iNetVu®

by C-COM Satellite Systems Inc.

## TECHNICAL SPECIFICATIONS



### Electrical

Tx & Rx cables	2 RG6 cables (10 m each)	
Control Cables	Standard	
	Optional	10m Ext. Cable upto 75m available
Transmit (Tx) Power	1 to 200 Watt (Ku band) *	
Transmit (Tx) Frequency	13.75 – 14.50 GHz (Ku Band)	
Receive (Rx) Frequency	10.95 – 12.75 GHz (Ku Band)	
Midband Gain		
Rx	41.5 dBi	
Tx	43.0 dBi	
Antenna Noise Temperature		
20° Elevation	46° K	
30° Elevation	43° K	
Sidelobe Envelope, Co-Pol (dBi)	Receive	Transmit
	1° < Ø < 20°	29 - 25 Log Ø dBi
	20° < Ø < 26.3°	- 3.5 dBi
	26.3° < Ø < 48°	32 - 25 Log Ø dBi
	48° < Ø	- 10 dBi (averaged)
Cross-Polarization		
Within 1 dB contour	-30 dB Max.	
Any Angle off Axis	-25 dB Max.	
VSWR	1:3:1 Max.	

### Mechanical

Reflector	1.2 m Prime Focus, Offset Feed
Mount Geometry	Elevation over Azimuth
Deployment Sensors	GPS antenna
	Compass ± 2°
	Tilt sensor ± 0.2°

### Physical

Mounting Plate	L: 52" (1321mm) W: 22" (559mm)
Stowed Dish Ext. Dims	L: 69.75" (1771mm) W: 48.6" (1235mm)
	H: 19.25" (488mm)
Deployed Height	66" (1676 mm) Max.
Reflector Weight	35 lbs (15.9 kg)
Total Weight w/ Reflector	204 lbs (92.5 kg)

\* Depending on size and weight for feed arm mounting limitation

### Environmental Survival

Wind Deployed	70 mph (112 km/h)
Wind Stowed	140 mph (225 km/h)
Temperature	-40°F to 150°F (-40°C to 65°C)

### Operational

Wind	45 mph (72 km/h)
Temperature	-26°F to 130°F (-32°C to 55°C)

### RF Interface

Radio Mounting	Feed Arm / Rear of Base / Inside Vehicle
Axis Transition	Twist-Flex Waveguide
Waveguide	WR75 Cover Flange Interface
Coaxial	RG6U from Feed Arm to Base Connector
Feed	2 port Xpol

### Motors

Electrical Interface	12V DC 15A max.
----------------------	-----------------

### Maximum Mount Rotation

Azimuth	Full 360° in overlapping 200° sectors
Elevation	0 - 85°
Polarization	±90°
Elevation Deploy Speed	Variable 2°/sec typ
Azimuth Deploy Speed	Variable 15°/sec max, 10°/sec typ
Peaking Speed	0.2°/sec

### Note:

Systems are configured with Cross-Pol as standard, Co-Pol is optional.

Standard warranty: 2 years



[www.servsat.com](http://www.servsat.com)

Spanish: 770-757-1767 English: 770-754-4547

Specifications are subject to change

May 2010